





CARBON BLACK DISPERSION TESTER WITH CCD CAMERA UNIT
 MELT FLOW INDEX TESTER
 DENSITY GRADIENT TESTER (COLUMN METHOD) ○ ○ ○



Carbon Black Dispersion Tester

Projection	Microscope
Doom size	6" Dia.
Magnification Range	100 X, 200 X, 400 X.
Accuracy	± 0.5 %
Least Count	0.1 °C
Power Supply	230Vac/50Hz ±10%



Hot Plate

Plate Dia	8"
Temperature Range	300 Degree

Melt Flow Index Tester (Auto Cutter / Without Auto Cutter)

Temperature Range	400°C
Least Count	0.1°C
Temperature control	±0.1°C
Temperature sensor	RTD / PT 100 Sensor.
Timer accuracy	0.01 second
Power	Single Phase 100 / 120 / 220 / 240 V AC / 50/60 Hz. 1.2 kVA . Supply voltage fluctuation within ± 10 % of the set Value.

Density Gradient Column (Single / Double)

Column Working Length	700 MM
Column Jacketing	Acrylic
Floats	Glass
Stirrer	Magnetic
Power	Single Phase 100 / 120 / 220 / 240 V AC / 50/60 Hz. 1.2 kVA . Supply voltage fluctuation within ± 10 % of the set Value.



STOP KILLING WILDLIFE

www.deeshaimpex.com